



## SINGLE-SPLIT FLOOR STANDING TYPE


# SRF-ZS/ZSX

### Auto air outlet selection

In case both lower and upper air outlets can be selected.

### Installation workability

Piping and drain hose connection can be selected out of 6-directions.



Wireless  
remote control

SRC25ZS-W2, SRC35ZS-W2

SRC50ZSX-W2

## KEY FEATURES

- The elegant semi flat front panel in stylish white, fit various kinds of rooms and create relaxing atmosphere.
- Choice from wall hanging, floor standing or behind gallery installation is available.
- Low Global Warming Potential (GWP) and High energy efficiency by new refrigerant R32.
- Quiet Operation. The level of 25ZS-W in the cooling Ulo mode is only 25dB(A).
- The "flap control system" allows users to change flap angles and positions according to their preference. Flaps can be set at different angles.
- Allergen clear filter is equipped as a default.

## SPECIFICATIONS

| Indoor unit  |         |                         | SRF25ZS-W  | SRF35ZS-W              | SRF50ZSX-W              |
|--|---------|-------------------------|--|------------------------|-------------------------|
| Outdoor unit   |         |                         | SRC25ZS-W2   | SRC35ZS-W2             | SRC50ZSX-W2             |
| Power source   |         |                         | 1 Phase, 220 - 240V, 50Hz  |                        |                         |
| Nominal cooling capacity (Min~Max)                   |         | kW                      | 2.5 (0.9~3.1)  | 3.5 (0.9~4.1)          | 5.0 (1.1~5.6)           |
| Nominal heating capacity (Min~Max)                   |         | kW                      | 2.9 (0.8~3.7)  | 4.5 (0.8~5.2)          | 6.0 (0.8~7.4)           |
| Power consumption                                    |         | Cooling/Heating kW      | 0.59 / 0.66  | 0.82 / 1.12            | 1.32 / 1.58             |
| EER/COP  |         | Cooling/Heating         | 4.24 / 4.39  | 4.27 / 4.02            | 3.79 / 3.80             |
| Max. running current                                 |         | A                       | 9  | 9                      | 9                       |
| Sound power level                                    | Indoor  | Cooling/Heating         | 50 / 51  | 51 / 52                | 58 / 58                 |
|  | Outdoor | Cooling/Heating         | 59 / 60  | 63 / 64                | 63 / 62                 |
| Sound pressure level                                 | Indoor  | Cooling (Hi/Me/Lo/Ulo)  | 38 / 32 / 29 / 25  | 40 / 35 / 33 / 29      | 46 / 38 / 33 / 28       |
|  |         | Heating (Hi/Me/Lo/Ulo)  | 39 / 35 / 33 / 29  | 41 / 36 / 35 / 33      | 46 / 41 / 38 / 32       |
|  | Outdoor | Cooling/Heating         | 45 / 47  | 50 / 51                | 51 / 51                 |
| Air flow   | Indoor  | Cooling (Hi/Me/Lo/Ulo)  | 9.0 / 7.6 / 6.7 / 5.8  | 9.2 / 7.8 / 7.3 / 6.4  | 11.5 / 9.6 / 7.4 / 6.6  |
|  |         | Heating (Hi/Me/Lo/Ulo)  | 10.5 / 8.2 / 7.7 / 6.6   | 10.7 / 8.3 / 8.1 / 7.4 | 12.0 / 10.0 / 9.4 / 7.6 |
|  | Outdoor | Cooling/Heating         | 27.4 / 27.4  | 31.5 / 31.5            | 39.0 / 33.0             |
| Exterior dimensions                                  | Indoor  | HeightxWidthxDepth      | 600 x 860 x 238  |                        |                         |
|  | Outdoor | HeightxWidthxDepth      | 540 x 780(+62) x 290   |                        | 640 x 800(+71) x 290    |
| Net weight   |         | Indoor / Outdoor        | 18.0 / 31.0  | 19.0 / 34.5            | 19.0 / 45.0             |
| Refrigerant  |         | Type/GWP                | R32 / 675  |                        |                         |
|  |         | Charge                  | 0.62/0.419   |                        |                         |
| Refrigerant piping size                              |         | Liquid/Gas              | 6.35(1/4") / 9.52(3/8")  |                        | 6.35(1/4") / 12.7(1/2") |
| Refrigerant line (one way) length[chargeless length] |         | m                       | Max. 20 [10]   | Max. 20 [15]           | Max. 30 [15]            |
| Vertical height differences                          |         | Outdoor is higher/lower | Max. 10 / Max. 10  |                        | Max. 20 / Max. 20       |
| Outdoor operating temperature range                  |         | Cooling                 | -15~24   |                        |                         |
|  |         | Heating                 | -15~46   |                        | -20~24                  |
| Clean filter   |         |                         | Allergen Clear Filter x 1 Photocatalytic Washable Deodorising Filter x 1 |                        |                         |

\* The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

\* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

\* 'tonne(s) of CO<sub>2</sub> equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.